

PERFORATED TRAY WITHOUT DOWNCOMER,  
PERFORATED TRAY TOWER WITHOUT DOWNCOMER,  
AND  
METHOD OF DISTILLATION

FIELD OF THE INTENTION

The present invention relates to a perforated tray without downcomer, a perforated tray tower without downcomer, and a method of distillation, and in particular, relates to (1) a perforated tray without downcomer that enables stable distillation of an easily polymerizable compound, such as (meth)acrylic acid, and a liquid containing such an easily polymerizable compound (hereinafter, may be referred to collectively as "an easily polymerizable compound") over an extended period of time while effectively inhibiting the formation of polymers, (2) a perforated tray tower without downcomer

005674:0300

fitted with such perforated trays without downcomer, and (3) a method of distillation using the perforated tray tower without downcomer.

## BACKGROUND OF THE INVENTION

To manufacture commercial products, it is widely practiced in the manufacturing industry to distil and refine an easily polymerizable compound, such as (meth)acrylic acid or an ester thereof, in the presence of oxygen or a polymerization inhibitor for the purpose of preventing polymerization of the compound. Besides, it is well known that perforated trays without downcomer and a perforated tray tower without downcomer fitted with the trays are used for distillation.

Each perforated tray without downcomer disposed in such a perforated tray tower without downcomer has holes formed almost uniformly all over the tray, except for those holes for clamps, bolts, etc. that attach the tray to a support beam, a support ring, etc. Typically, the holes (perforations) are formed by a punching press or a drill. It is known that in a perforated tray without downcomer, specifications on, among other things, the hole diameter and the hole shape, the tray thickness, and the opening ratio, are very important factors in improving performance, as well as specifications on the

tray-to-tray interval and the levelness when the perforated tray without downcomer is disposed in the perforated tray tower without downcomer (See, *Properties of Perforated Trays Without Downcomer*, Vol. 34, Chemical Engineering, page 567 to 571, 1970, by Hashimoto et al, and *Distillation Engineering Handbook* published by Asakura Shoten 1966).

However, in some cases, distillation of, for example, (meth)acrylic acid, using the conventional perforated tray tower without downcomer causes formation of a polymer which should be removed manually or chemically after suspension of the operation.

Accordingly, to solve the above problems, techniques, each realizing a specific state, are suggested as follows to further inhibit polymerization during distillation using the perforated tray tower without downcomer. Each technique is aimed at improving inhibition of polymerization by using a polymerization inhibitor (stabilizer agent).

In a first state, the inside of the perforated tray tower without downcomer is wet with a liquid containing an easily polymerizable compound. This is aimed at bringing a gaseous phase portion into contact with a polymerization inhibitor by bringing the gaseous phase portion into contact with a liquid phase portion, because

005720" 2729560

[illegible][illegible][illegible][illegible]

disclose an example of a specific technique to effect the second state, whereby a support ring (perforated tray support member) is punched to form a hole through which the liquid on the support ring flows down smoothly. Japanese Laid-Open Patent Application No. 10-76103/1998 (Tokukaihei 10-76103) discloses another example of a specific technique to effect the second state, whereby the perforated trays without downcomer are separated from the tower wall by a distance of 1mm to 15 mm to prevent liquid currents from channelling and stagnating near the tower wall.

Each of these techniques is able to prevent the formation of polymers to some extent, but not sufficiently. The conventional techniques, although successfully effecting either the first state or the second state through an additional specified arrangement in the tower and perforated trays, fails to concurrently and surely effect both the states.

Another problem is that providing a jacket as above requires large investments in equipment and strict temperature controls, which is not very practical. Further referring to the jacket method above, the tower wall is not made wet (kept dry) so as to prevent the gas from condensing, thus effecting a state that is opposite to the first state.



intervals between, and the inclinations (levelness) of, the perforated trays without downcomer disposed in the tower, as well as the distance between the two most closely located holes when a plurality of perforated tray without downcomer is used at the same stage, are regulated in specific ranges, and (iii) the perforated tray tower without downcomer is used for distillation under specific conditions, which has led to the completion of the invention.

Specifically, in order to achieve the foregoing object, the perforated tray without downcomer in accordance with the present invention satisfies following conditions (a) to (d):

(a) The hole diameter,  $d$ , is in a range of from 10mm to 25mm.

(b) The center-to-center distance between two adjacent holes is in a range of from  $1.2d$  to  $3d$ .

(c) The tray thickness is in a range of from 2mm to 8mm.

(d) The opening ratio is in a range of from 10% to 30%.

Further, the perforated tray tower without downcomer in accordance with the present invention is fitted with two or more such perforated trays without downcomer and satisfies following conditions:

00505743-024000

(g) The interval between the perforated trays without downcomer is in a range of from  $0.1D$  to  $0.5D$ , where  $D$  is the tower diameter.

(h) The levelness of the perforated tray does not exceed 8mm.

(i) The two most closely located holes that belong respectively to adjacent perforated trays without downcomer are separated by a distance ranging from 50mm to 150mm when a plurality of perforated trays without downcomer are used at the same stage.

Further, the method of distillation in accordance with the present invention is a method to distil an easily polymerizable compound or a liquid containing an easily polymerizable compound, using the perforated trays without downcomer.

Distillation of an easily polymerizable compound by means of specified perforated trays without downcomer or perforated tray tower without downcomer satisfying the foregoing conditions have at least following advantages:

(1) The gas and liquid flow uniformly on the perforated tray without downcomer with a smaller gradient in liquid concentration and a more uniform dispersion in concentration of polymerization inhibitors.

(2) The gas and liquid flow smoothly without channelling, and stagnate for a relatively short period

00506712 024500



of time.

(3) The perforated tray without downcomer and the inner walls of the tower are wet with a liquid containing a polymerization inhibitor. The inside of the tower is therefore almost completely wet with no parts being left dry.

(4) The liquid does not stagnate on the perforated tray without downcomer.

According to the present invention and its advantages described above, both the first state and the second state are concurrently and surely effected with the formation of polymers being effectively prevented.

For a fuller understanding of the nature and advantages of the invention, reference should be made to the ensuing detailed description taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a cross-sectional view showing an arrangement of a perforated tray without downcomer of an embodiment in accordance with the present invention.

Figure 2(a) to Figure 2(e) are explanatory drawings showing variations of the cross-section of a hole shape of the perforated tray without downcomer shown in Figure 1.

00506743:024800

Figure 3 is an explanatory drawing showing an example of a cross-section of a perforated tray tower without downcomer, in accordance with the present invention, fitted with perforated trays without downcomer that are identical to that shown in Figure 1.

Figure 4 is an explanatory drawing showing assembly of an extended perforated tray from a plurality of perforated trays without downcomer disposed at the same stage.

Figure 5(a) is an explanatory drawing showing an arrangement of connecting sections of adjacent perforated trays when a plurality of perforated trays are used at the same stage in the perforated tray tower without downcomer shown in Figure 4, and Figure 5(b) is an explanatory drawing showing a center-to-center distance ( $L_2$ ) between the two most closely located holes that respectively belong to the adjacent perforated trays.

Figure 6(a) and Figure 6(b) are explanatory drawings illustrating arrangements of a connecting section between perforated trays: Figure 6(a) corresponds to a cross-sectional view taken along line B-B in the extended perforated tray shown in Figure 4 and Figure 5(a), and Figure 6(b) corresponds to a cross-sectional view taken along line A-A in the extended perforated tray shown in Figure 4 and Figure 5(a).

Figure 7 is an explanatory drawing showing, in the perforated tray tower without downcomer shown in Figure 3, a hole of the perforated tray at the upper stage, which is used as a basis in calculating the blind ratio, overlapping a hole of the perforated tray at the lower stage.

Figure 8 is an explanatory drawing showing, in the extended perforated tray shown in Figure 4, the orientation of the tray at an even numbered tray in relation to that at an odd numbered tray.

#### DESCRIPTION OF THE EMBODIMENTS

Referring to drawings, the following will discuss an embodiment in accordance with the present invention. Note that hereinafter in some cases the perforated tray without downcomer will be referred to simply as the perforated tray, and the perforated tray tower without downcomer as the tower.

Figure 1 is an explanatory drawing showing a perforated tray without downcomer 1, that is an embodiment of the present invention. As shown in Figure 1, the perforated tray 1 in accordance with the present invention is perforated with a plurality of holes 2 that have substantially equal diameters and are mutually separated by substantially equal distances that satisfy

condition (b) below. As to the holes 2, conditions (a) to (d) are specified:

(a) The hole has a diameter,  $d$ , in a range of from 10mm to 25mm, and preferably in a range of from 12mm to 22mm.

(b) The hole 2 is separated from an adjacent hole 2 by a distance,  $L1$ , in a range of from  $1.2d$  to  $3d$ , and preferably, in a range of from  $1.5d$  to  $2.5d$ , where the distance  $L1$  is measured as the distance between the centers of the two holes 2.

(c) The tray has a thickness in a range of from 2mm to 8mm, and preferably, in a range of from 2mm to 4mm.

(d) The opening ratio is in a range of from 10% to 30%, and preferably, in a range of from 12% to 27%.

In the present invention, the opening ratio is defined as a ratio (percentage points) of the sum of the areas of the holes 2 of the perforated tray 1 to the horizontal cross-sectional area of the tower (perforated tray tower without downcomer) in which the perforated tray 1 is disposed. Accordingly, the opening ratio is given by the equation:

$$\text{Opening Ratio (\%)} = (P/Q) \times 100$$

where  $P$  is the sum of the areas of the holes 2 (the holes 2 as a whole will be collectively referred to as an opening section), and  $Q$  is the horizontal cross-sectional



currents. A center-to-center distance L1 exceeding 3d causes liquid currents to stagnate in the extended space created between adjacent holes 2, and increase the likelihood of polymerization occurring.

A tray thickness of less than 2mm allows the perforated tray 1 to vibrate and thereby causes a liquid gradient to develop on the perforated tray 1, and increases the likelihood of parts of the perforated tray 1 drying up. A tray thickness exceeding 8mm causes liquid currents to stagnate in the holes 2, and increases the likelihood of polymerization occurring.

Supposing that the hole diameter is fixed to a certain value, an opening ratio of less than 10% causes liquid currents to stagnate, and increases the likelihood of polymerization occurring; by contrast, an opening ratio exceeding 30% segregates gas and liquid currents, and increases the likelihood of polymerization occurring.

In the technology using perforated trays without downcomer 1 in accordance with the present invention, an easily polymerizable compound is subjected to a gas and liquid contact by allowing some of the liquid to fall down through the holes 2 and the gas to go up through the holes 2 while holding some of the liquid on the perforated tray 1. So, the liquid and gas currents through the holes 2 need to be controlled so as to create

0057429560



2(a). The warping protrusion 2b, if left as it is, disrupts smooth liquid currents and increases the likelihood of polymerization occurring.

Accordingly, as to the perforated tray 1 in accordance with the present invention, the protrusion 2b is preferably removed. More preferably, the hole edge 2a is fabricated into a smooth, round shape, either on the upper side or on the lower side as shown in Figure 2(b), or on both sides. The dimensions and shape of the round edge is not restricted in any manner, provided that it facilitates the down currents of the liquid: Figure 2(d) shows such an example where the hole edge 2a is cut into an angular shape. Furthermore, the smooth, round edge, although preferable, is not always essential: the hole edges 2a may be flat, instead of being round and smooth, both on the upper side and on the lower side as shown in Figure 2(e).

Based on the foregoing, in the perforated tray without downcomer 1 in accordance with the present invention, in addition to conditions (a) to (d), at least one of following conditions (e) and (f) is satisfied. By satisfying all these conditions, the first and second states are better effected; hence the formation of polymers are more effectively prevented in the distillation of an easily polymerizable compound.



(e) The surface of the perforated tray 1 is substantially flat.

(f) The edge of the hole 2 is rounded at least either on the upper side or on the lower side.

Note that among conditions (a) to (f), the satisfaction of condition (b) is particularly preferred and gives advantages to the perforated tray without downcomer 1 in accordance with the present invention over conventional technology.

The following will discuss a perforated tray tower without downcomer in accordance with the present invention. A perforated tray tower without downcomer 3 in accordance with the present invention, as shown in Figure 3, is fitted with two or more perforated trays 1 that are configured like shelves according to the conditions specified below.

(g) The perforated trays 1 disposed respectively at vertically adjacent spacing are separated by an interval  $H$  in a range of from  $0.1D$  to  $0.5D$ , where  $D$  is the tower diameter.

(h) Each perforated tray 1 has a levelness not exceeding 8mm, preferably not exceeding 4mm. That is, the levelness is preferably less than 8mm, and more preferably less than 4mm.

(i) If a plurality of perforated trays 1 are used at



the condenser. Part of the liquid is withdrawn, while the rest is reintroduced into the tower 3 through the reflux 3c.

The liquid outlet 3e is connected to a reboiler (not shown). The easily polymerizable compound (liquid) is withdrawn from the tower 3 through the liquid outlet 3e. Part of the liquid is withdrawn, while the rest is fed to the reboiler where the liquid is boiled again. The reboiled easily polymerizable compound, including mixture of gas and liquid, is reintroduced to the tower 3 through the vapor inlet 3b.

The arrangement to supply and reintroduce the gas and liquid of the easily polymerizable compound into the tower explained above is intended to be a mere example; no constraints are imposed on the arrangement, and any conventional arrangement can be suitably used in place of this example.

If the interval H by which the perforated trays 1 disposed respectively at vertically adjacent spacing are separated in the tower 3 (see Figure 3) is less than  $0.1D$  (i.e., less than 10% of the tower diameter), gas currents are likely to channel, increasing the likelihood of polymerization occurring. If the interval H exceeds  $0.5D$  (i.e., 50% of the tower diameter), the gas currents stagnate for too long a time, increasing the likelihood

0050574 02400  
0050574 02400

of polymerization occurring in a gaseous phase portion.

If the levelness of the perforated tray 1 exceeds 8mm, the liquid gradient grows on the perforated tray 1 and causes gas and liquid currents to channel in a relatively large scale, increasing the likelihood of polymerization occurring. The levelness is defined as the difference between the highest and lowest points in a perforated tray 1. The levelness is measured by an ordinary method using a water manometer.

No particular constraints are imposed on the perforated tray 1 in accordance with the present invention in terms of its shape; the perforated tray 1 may be, for example, of a semicircular, partially deformed circular, sectorial, or square shape, as well as of the circular shape shown in Figure 1.

When the perforated tray tower without downcomer 3 has a relatively large diameter, two or more perforated trays 1 are typically disposed at the same stage as shown in Figure 4, with the installation through a manhole being taken into consideration. In other words, an extended perforated tray 11 is assembled from a plurality of perforated trays 1. When this is the case, the perforated trays 1 may either share an identical shape or have different shapes; for example, some of the perforated trays 1 have partially deformed circular











provides better control over gas and liquid currents through the holes 2 of the perforated trays 1 in distillation of an easily polymerizable compound as previously mentioned. Moreover, in a case when a plurality of perforated trays 1 are disposed at various stages, since conditions are specified on each of the plurality of perforated trays 1, it is ensured that the inner surfaces of the tower 3 is wet.

Consequently, if all conditions (g) to (i) are satisfied, both the first state where the inner surfaces of the tower 3 are wet with liquid and the second state where gas and liquid currents are prevented from channelling and stagnating are surely effected. So, the gaseous phase portion is always kept in contact with a polymerization inhibitor by subjecting it to gas and liquid contact, and the polymerization inhibitor is dispersed sufficiently as a result of the currents being prevented from channelling and stagnating; therefore, polymerization is better inhibited. For these reasons, the formation of polymers are effectively prevented.

In the perforated tray tower without downcomer 3 in accordance with the present invention, the two or more perforated trays 1 preferably satisfy condition (j) whereby the blind ratio, as defined in the following, is specified to 0.2 or larger, preferably 0.4 or larger, and

00506743:024800

more preferably 0.6 or larger.

For example, as shown in Figure 7, the holes 2, of a perforated tray 1 located at an upper stage, illustrated by solid lines partially overlap the holes 2, of a perforated tray 1 located at a lower stage, illustrated by dotted lines; accordingly, overlapping areas and non-overlapping areas (illustrated by slanted lines) are created in the holes 2 of the two perforated trays 1. In the present invention, the blind ratio of a perforated tray 1 is defined in relation to an immediately adjacent perforated tray 1 as the sum of the non-overlapping areas in the holes 2 of the perforated tray 1 divided by the sum of both the overlapping and non-overlapping areas of the holes (opening sections) 2 of the perforated tray 1.

Accordingly, in the present invention, the "blind ratio" of the perforated trays 1 disposed respectively at vertically adjacent spacing is given by the following equation:

$$\text{Blind Ratio} = 1 - (S/T)$$

where S is the sum of the areas (illustrated by slanted lines in Figure 7) where the holes 2 of the upper perforated trays 1 overlap the holes 2 of the lower perforated tray 1, and T is a smaller one of the sum of the areas of the holes 2 of the upper perforated tray 1



an easily polymerizable compound.

When a plurality of identical extended perforated trays 11, one of which is shown in Figure 4, are installed in a perforated tray tower without downcomer 3 in accordance with the present invention, in order to satisfy condition (j), those extended perforated trays 11b at even numbered trays (corresponding to the perforated trays 1b in Figure 3) are preferably orientated about 90° out of alignment with those extended perforated trays 11a at odd numbered trays (corresponding to the perforated trays 1a in Figure 3); an example of such a configuration is shown in Figure 8.

The disorientation angle to satisfy condition (j) is not limited in any particular manners, and may vary appropriately depending on the shape of the perforated trays 1 constituting the extended perforated trays 11. The disorientation angle of about 90° is suitable when a circular extended perforated tray 11 is constituted chiefly from a plurality of substantially rectangular perforated trays 1 as shown in Figure 4; if the perforated trays 1 have other shapes, other disorientation angles would be appropriate accordingly. Therefore, in the present invention, to satisfy condition (j), the extended perforated trays 11 (i.e., perforated trays 1) only need to be positioned in different

00505713-024900

orientations. Specific angles by no means affect the scope of the invention.

In the present invention, two or more perforated trays 1 satisfying the foregoing conditions may be disposed so as to satisfy at least either condition (i) or condition (j). This arrangement also gives a sufficient advantage to a perforated tray tower without downcomer 3 in accordance with the present invention.

A method of distillation in accordance with the present invention is for use in distillation of an easily polymerizable compound in the perforated tray tower without downcomer 3; therefore, a method of distillation in accordance with the present invention is implemented using a perforated tray tower without downcomer 3 fitted with two or more perforated trays without downcomer 1 that satisfy conditions (a) to (d), preferably satisfy further condition (e), and more preferably satisfy further condition (f), in such a manner to satisfy conditions (g) to (i) and preferably to satisfy further condition (j).

The method of distillation in accordance with the present invention is suitably used for distillation of an easily polymerizable compound or a liquid containing an easily polymerizable compound. Typical easily polymerizable compounds include (meth)acrylic acid as

0050674 024900

well as esters of (meth)acrylic acid, such as methyl (meth)acrylate, ethyl (meth)acrylate, n-butyl (meth)acrylate, and hydroxypropyl (meth)acrylate. The distillation as defined in the present invention includes an operation to purify a crude, easily polymerizable compound through distillation, an operation to separate and remove a predetermined compound from a liquid containing an easily polymerizable compound through distillation, etc.

In the method of distillation in accordance with the present invention, preferably either one of conditions (k) and (m) detailed below are satisfied, and more preferably both conditions are satisfied.

(m) The amount of wetting liquid with respect to the sum of the areas of the holes 2 is  $1\text{m}^3/\text{m}^2\cdot\text{h}$  or higher, preferably  $3\text{m}^3/\text{m}^2\cdot\text{h}$  or higher.

This arrangement prevents the formation of polymers more effectively. The amount of wetting liquid is here defined as the volume  $[m^3]$  of liquid supplied onto the perforated tray 1 per hour divided by the tower's cross-sectional area or the sum of the areas of the holes 2.

If the amount of wetting liquid is less than  $0.3m^3/m^2 \cdot h$  with respect to the tower's cross-sectional area or less than  $1m^3/m^2 \cdot h$  with respect to the sum of the areas of the holes 2, parts of the perforated tray 1 dry, and the stabilizer agent is not evenly distributed, increasing the likelihood of polymerization occurring.

In other words, in the method of distillation in accordance with the present invention, if condition (k) or (m) is satisfied, it is ensured that the inner surfaces of the tower 3 are wet, and the amount of wetting liquid is suitable; therefore, the liquid can be stored on the perforated tray 1 at an appropriate amount, causing suitable gas and liquid currents through the holes 2. In short, if the condition (k) and/or (m) is/are satisfied, it is ensured that both the first state where the inner surfaces of the tower 3 is wet with liquid and the second state where gas and liquid currents are prevented from channelling and stagnating are satisfied; therefore the formation of polymers is even more effectively prevented.

In the following, specific examples and comparative examples will be presented to illustrate the present invention in more detail. The following examples and comparative examples will present best modes each satisfying all of conditions (a) to (k) and (m), which by no means limit the scope of the present invention. In other words, in the present invention, at least an essential condition(s) among the foregoing conditions should be satisfied in accordance with various alternatives in distillation as previously mentioned.

[Example 1]

Acrylic acid was distilled using a perforated tray tower without downcomer satisfying conditions (g) to (j) fitted with perforated trays without downcomer satisfying conditions (a) to (d), as well as having holes 2 each of which is flat at its edge on its upper side and rounded at its edge on the lower side (i.e., satisfying conditions (e) and (f)), according to a method satisfying conditions (k) and (m).

Condition (a): Hole Diameter  $d = 18\text{mm}$

Condition (b): Center-to-center Distance  $L_1$  between Adjacent Holes  $c = 32\text{mm}$

Condition (c): Tray Thickness = 3mm

Condition (d): Opening Ratio = 18%



Condition (g): Interval between Perforated Trays  $H = 0.25D$  (D: Tower Diameter)

Condition (h): Levelness = 3mm

Condition (i): Center-to-center distance between Two Most Closely Located Holes that Respectively Belong to Adjacent Perforated Trays  $L_2 = 80\text{mm}$

Condition (j): Blind Ratio = 0.65

Condition (k): Amount of Wetting Liquid (with respect to Tower's Cross-sectional Area) =  $1.0\text{m}^3/\text{m}^2 \cdot \text{h}$

Condition (m): Amount of Wetting Liquid (with respect to Sum of Areas of Holes) =  $5.0\text{m}^3/\text{m}^2 \cdot \text{h}$

That is, a liquid composed of 85 percent by weight acrylic acid and 14 percent by weight acetic acid was fed at a mid-stage of the tower that was fitted with 30 trays, and the system was operated at a tower top pressure of 5.3kPa absolute (40mmHg) and a tower top temperature of 44°C continuously for two months. Hydroquinone was added as a polymerization inhibitor through a tower top an amount of 100ppm for tower top vapor flow rate. Further, an oxygen-containing gas was supplied a predetermined amount into the tower bottom. After completion of the operation, the tower interior was inspected: results are shown in Table 1.

[Comparative Examples 1 to 13]

Acrylic acid was distilled in the same manner as example 1, except that conditions (a) to (f) for the perforated trays without downcomer, conditions (g) to (j) for the perforated tray tower without downcomer, and condition (k) for the distillation operation were changed as shown underlined in Table 1; results of comparative examples 1 to 12 are all shown in Table 1. Condition (m) for the distillation operation can be calculated by the following equation:

$$\text{Condition (m)} = \frac{\text{Amount of Wetting Liquid}}{\{(\text{Opening Ratio}) / 100\}}$$

where the amount of wetting liquid is given in condition (k) and the opening ratio is given in condition (d).

00506742 034300

Table 1

Conditions	a	b	b/a	c	d	e·f	g	h	i	j	k	m	*1
Units	mm	mm	-----	mm	%	-----	%	mm	mm	----	*2	*2	kg
Example 1	18	32	1.78	3	20	Fig.2(b)	25	80	80	0.65	1	5.0	0.7
Comparative Example 1	8	12	1.50	3	10	Fig.2(b)	25	80	80	0.65	1	10.0	11.3
Comparative Example 2	30	90	3.00	3	20	Fig.2(b)	25	80	80	0.65	1	5.0	2.6
Comparative Example 3	18	60	3.33	3	10	Fig.2(b)	25	80	80	0.65	1	10.0	0.7
Comparative Example 4	18	32	1.78	9	20	Fig.2(b)	25	80	80	0.65	1	5.0	28.9
Comparative Example 5	18	50	2.78	3	8	Fig.2(b)	25	80	80	0.65	1	12.5	29.6
Comparative Example 6	18	22	1.22	3	32	Fig.2(b)	25	80	80	0.65	1	3.1	4.0
Comparative Example 7	18	32	1.78	3	20	Fig.2(b)	8	80	80	0.65	1	5.0	10.1
Comparative Example 8	18	32	1.78	3	20	Fig.2(b)	55	80	80	0.65	1	5.0	7.9
Comparative Example 9	18	32	1.78	3	20	Fig.2(b)	25	9	80	0.65	1	5.0	48.2
Comparative Example 10	18	32	1.78	3	20	Fig.2(b)	25	160	160	0.65	1	5.0	15.2
Comparative Example 11	18	32	1.78	3	20	Fig.2(b)	25	80	80	0.15	1	5.0	17.6
Comparative Example 12	18	32	1.78	3	20	Fig.2(b)	25	80	80	0.65	0.15	0.8	20.9
Comparative Example 13	18	32	1.78	3	20	Fig.2(a)	25	80	80	0.65	1	5.0	5.8

\*1: Weight of Polymer

\*2:  $m^3/m^2 \cdot h$

As clearly understood from Table 1 above, polymers are formed in an amount of less than 1kg in the distillation of acrylic acid if conditions are satisfied in accordance with the present invention, and by contrast, in an amount of over 2.5kg if conditions are not satisfied in accordance with the present invention.

As discussed so far, by using perforated trays without downcomer and perforated tray tower without downcomer satisfying those conditions above in accordance with the present invention or using a method of distillation in accordance with the present invention, it is ensured that the first state and the second state are concurrently effected; an easily polymerizable compound and a liquid containing an easily polymerizable compound can be distilled in a stable manner over an extended period of time, while effectively preventing the formation of polymers.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art intended to be included within the scope of the following claims.

0034290300

11

1.

the plurality of perforated trays without downcomer disposed respectively at vertically adjacent spacing have a blind ratio of 0.2 or higher.

*[Handwritten signature]*

the plurality of perforated trays without downcomer disposed respectively at vertically adjacent spacing have a blind ratio of 0.2 or higher.

~~8. A perforated tray tower without downcomer, comprising a plurality of perforated trays without downcomer, each of the plurality of perforated trays~~

wherein, if one or more of the plurality of perforated trays without downcomer are used at the same stage, the two most closely located holes that respectively belong to adjacent perforated trays are separated from one another by a center-to-center distance in a range of from 50mm to 150mm.

the perforated tray without downcomer has an opening ratio in a range of from 10% to 30%, and

each of the plurality of holes is separated from an adjacent hole by a center-to-center distance in a range of from  $1.2d$  to  $3d$ ,

wherein, if one or more of the plurality of perforated trays without downcomer are used at the same stage, the two most closely located holes that respectively belong to adjacent perforated trays are separated from one another by a center-to-center distance in a range of from 50mm to 150mm.

10. The method of distillation as defined in claim 9, wherein

at least one of first and second conditions is satisfied,

the first condition being such that an amount of wetting liquid with respect to a cross-sectional area of the tower is  $0.3\text{m}^3/\text{m}^2 \cdot \text{h}$  or higher, and

the second condition being such that an amount of wetting liquid with respect to a sum of areas of the plurality of holes is  $1\text{m}^3/\text{m}^2 \cdot \text{h}$  or higher.

11. The method of distillation as defined in claim 9, wherein

an easily polymerizable compound or a liquid containing an easily polymerizable compound is distilled.

the easily polymerizable compound is at least one compound selected from the group consisting of (meth)acrylic acid and esters thereof.

at least one of first and second conditions is satisfied,

the second condition being such that an amount of wetting liquid with respect to a sum of areas of the plurality of holes is  $1\text{m}^3/\text{m}^2 \cdot \text{h}$  or higher.

~~Red~~